

**STA - S - 025 - B - P3 - U - LTB - 1**

Model Code
STA - Stauff Accumulator

Type
<b>S</b> ASME Type - North American (Standard)
<b>E</b> European Type (optional)

Accumulator Model				
Size	Capacity	3000 PSI Bottom Repairable	3000 PSI Top Repairable	5000 PSI Bottom Repairable
<b>1 Qt.</b>	1 Quart	X	N/A	N/A
<b>010</b>	1 Gallon	X	N/A	C/F
<b>025</b>	2.5 Gallon	X	X	X
<b>050</b>	5 Gallon	X	X	X
<b>100</b>	10 Gallon	X	C/F	X
<b>110</b>	11 Gallon	X	X	N/A
<b>150</b>	15 Gallon	X	C/F	C/F

Style
<b>B</b> Bottom Repairable (3000 & 5000 PSI)
<b>T</b> Top Repairable (3000 PSI Only)

Pressure Rating
<b>P 3</b> 3000 PSI/ 207 bar (Bottom and Top Repairable)
<b>P 5</b> 5000 PSI / 345 bar (Bottom Repairable Only)

Fluid Port Connection
<b>U</b> SAE Thread (Standard)
<b>N</b> NPT Thread (Optional - Available with SAE-NPT Adaptor) See page A52
<b>F1</b> Code 61 Split Flange (Optional-Available with Split Flange Adaptor) See page A52
<b>F2</b> Code 62 Split Flange (Optional-Available with Split Flange Adaptor) See page A52

Bladder Material
<b>LTB</b> Low Temp. Buna (Standard)
<b>N</b> Buna (Optional)
<b>V</b> Viton (Optional)
<b>E</b> EPR (Optional)

Design Code
<b>1</b> Standard (* = Special design No. to be assigned)

= Shaded Area denotes Standard Stock Items. C/F = Consult Factory for Availability

ACCESSORIES