



A variety of standard and custom PPC-04/06/08/12-Kits can be supplied to meet customer requirements. All kits are supplied in a handy case including individual foam inserts, which provide room for the following components:



- 1 Hydraulic Tester PPC-04 /2
- 1 Power supply
- up to 3 Pressure transducers with adapter STAUFF-Test 20
- up to 3 Connection Cable
- 1 Temperature sensor with straight fitting SGV-J3/4-G (not shown here)
- 3 Adapters for STAUFF-Test series 15, 12 and 10 are supplied with each PPC-04 /2-Kit
- 1 Operators manual

- 1 Hydraulic Tester PPC-06, PPC-08 or PPC-12
- 1 Power supply
- up to 3 Pressure transducers with adapter STAUFF-Test 20
- up to 3 Connection Cable
- 1 Temperature sensor (optional)
- 3 Adapters for STAUFF-Test series 15, 12 and 10 are supplied with each PPC-06/08/12-Kit
- 1 Operators manual
- 1 PC-Software for PPC-06/08/12
- 1 PC-connection cable

PPC - 04 - AP - 3 T - * / *** / *****

PPC	Hydraulic Tester
04-B-SET	2 sensor inputs, without internal storage Battery-powered
04-A-SET	2 sensor inputs, without internal storage, with rechargeable battery and power supply, without data-output
04-AP-SET	2 sensor inputs, without internal storage, with rechargeable battery and power supply, with data-output
06-SET	3 sensor inputs, incl. PC-software and PC- connection cable, internal data storage, for up to 60.000 MIN-/MAX-data points
08-SET	4 sensor inputs, incl. PC-software and PC- connection cable, internal data storage, for up to 125.000 MIN-/MAX-data points
12-SET	6 sensor inputs, incl. PC-software and PC- connection cable, internal data storage, for up to 250.000 MIN-/MAX-data points

Pressure Range for Pressure Transducer	
000/015/100/ 400/600	Pressure range for pressure transducer No.3
For Kits with only two pressure transducers please fill in "000" for the third pressure transducer	
015/100/ 400/600	Pressure range for pressure transducer No.2
015/100/ 400/600	Pressure range for pressure transducer No.1
Please Note: in order to measure differential pressure two transducers of the same pressure range must be used.	

Number of Pressure Transducers	
1	with one pressure transducer
2	with two pressure transducers
3	with three pressure transducers

Temperature Sensor	
	without temperature sensor
T	with temperature sensor

Note: Maximum three sensors (pressure transducers and temperatures sensor) are allowed for one PPC-06/08/12-Kit at the same time.